

Reflex CASTORS AND WHEELS

Fitting Options / accessories

REFLEX
equip

2 of 2

Pintle Bolts



with Expanding Adaptors




with M12 Threaded Tube Ends



Round M12 Threaded Tube Ends
Square M12 Threaded Tube Ends
Rectangular M12 Threaded Tube Ends
[Click here to view Tube Ends](#)

with 1/2" Solid Pintles



The -AS22 stem consists of the 19mm (3/4") round solid stem, fitted with a square nylon sleeve

Bolt Hole
12mm
1/2"

Note:
Can be changed to
8mm or
10mm with
reducing
bushes
Part
numbers:
RB 1/2-08
RB 1/2-10

			Code		Shape	Material	Size	Tube Size I.D. Range
			Steel	Stainless				
Code	Part	Size (diameter x length)	-ER19	-ER19SS	Round	Nylon	19mm	18.5 - 21.0
-E	Bolt only	M12x81 Standard (0.5" x 3.187")	-ER22	-ER22SS	Round	Nylon	22mm	21.5 - 24.0
-ESS	Bolt only	M12x65 Stainless Stl (0.5" x 2.562")	-ER22R	-ER22RSS	Round	Rubber	22mm	21.5 - 24.0
-E12x35	Bolt only	M12x35 (0.5" x 1.375")	-ER28	-ER28SS	Round	Nylon	28mm	25.0 - 28.0
-E12x40	Bolt only	M12x40 (0.5" x 1.562")	-ES19	-ES19SS	Square	Nylon	19mm	18.5 - 21.0
-E12x45	Bolt only	M12x45 (1/2" x 1 3/4")	-ES22	-ES22SS	Square	Nylon	22mm	21.5 - 24.0
-E12x50	Bolt only	M12x50 (1/2" x 2")	-ES22R	-ES22RSS	Square	Rubber	22mm	21.5 - 24.0
-E12x55	Bolt only	M12x55 (1/2" x 2 1/8")	-ES28	-ES28SS	Square	Nylon	28mm	21.5 - 24.0
-E12x65	Bolt only	M12x65 (0.5" x 2.562")	Expanding adaptors can confidently be used on castors up to 125mm (5") wheel diameter and 150kg (330lb) load capacity (and up to 200mm (8") castors only at lighter usage and loads <80kg). The castor and adaptor are ordered as two separate items e.g. MSQ125G/MZH (castor) AND (on the next line) -ER22 (the pintle and adaptor). The factory will assemble them prior to despatch. If ordering the above castor with the stem only (no adaptor required) The order should read: MSQ125G/MZH (castor) AND (on the next line) -E the pintle only. The factory will assemble them prior to despatch. If ordering the adaptor as a spare part add 'SP-ADAP' to the part number, i.e. SP-ADAPER22.					
-E 1/2x30	Bolt only	1/2" UNF x 1 1/8"						
-E 1/2x40	Bolt only	1/2" UNF x 1 9/16"						
-E 1/2x50	Bolt only	1/2" UNF x 2"						

Code	Stem O.D.	Tube Size OD x wall	Cross Drill Hole distance from end x hole diameter
-AR19	19.0mm round	22 x 1.2mm	19.0 x 8mm (0.852" x 5/16")
-AR22	22.0mm round	25 x 1.6mm	19.0 x 8mm (1" x 5/16")
-AS22	-AR19 with adaptor 22.0mm square	25 x 1.6mm SQ	19.0 x 8mm (0.852" x 5/16")
-AR28	-28.0mm round	32 x 1.6mm	19.0 x 8mm (3/4" x 5/16")

The castor and pintle are ordered as two separate items e.g. MSQ125G/MZH (castor) AND (on the next line) -AR22 (the pintle). The factory will assemble them prior to despatch. If ordering the pintle only, add 'SP' (spare part) to the part number e.g. SP-AR22.

All rights reserved Fallshaw Pty Ltd 2008

www.reflexequip.com.au

MELBOURNE
(03) 9763 9644
rowville@reflexequip.com.au

SYDNEY & ILLAWARRA
(02) 9725 3266
smithfield@reflexequip.com.au

CENTRAL COAST & NEWCASTLE
(02) 4324 3455
gوسفord@reflexequip.com.au

REFLEX