

# Reflex CASTORS AND WHEELS

150kg 300lb

REFLEX  
equip



## The quality standard

- 5 year warranty on fork
- 3 year warranty on wheel
- CoreCoat™ lacquer provides 3 times the Australian Standard for corrosion protection
- Excellent design and performance

### NOTES:

- For chrome plating see [M.Deluxe](#)
- If swept radius is too large a shorter pedal is [available](#)
- Black or grey pedal & seal colour [available](#)

### Fork Options

| Mount Type | ISO Plate   |   | North American (NA) Plate |   | Bolt hole |                       |
|------------|---|---|---------------------------|---|-----------|-----------------------|
|            | Diagram   | Dimensions  | Diagram                   | Dimensions                                | Diagram   | Dimensions            |
|            |   | 60/44<br>73/8 1 1/4<br>80/76 3 1/8 3/8<br>96 3 13/16<br>78 3 1/16 |                           | 44<br>76/67 3 3/8<br>95 3 3/4<br>70 2 3/4 |           | 12.7 1/2<br>68 2 1/16 |
|            | Fitted standard with ISO mount plate eg. MTQ150G/MZPTB.<br>For North American plate add N after the fork code. eg. MTQ150G/MZPNTB |   |                           |   |           |                       |

Can be fitted with 1/2" or M12 bolt mounts  
with solid pintles (recommended)  
or expanding adaptors (at lighter usage/loads <80kg)

[Fitting Options](#)

| Fork Size    | 150   | 175     | 200    | 150 | 175 | 200    | 150 | 175 | 200    | 150   | 175     | 200    | 150 | 175 | 200    | 150 | 175 | 200    |
|--------------|-------|---------|--------|-----|-----|--------|-----|-----|--------|-------|---------|--------|-----|-----|--------|-----|-----|--------|
| Mount Height | 187   | 214     | 238    | 187 | 214 | 238    | 187 | 214 | 238    | 187   | 214     | 238    | 187 | 214 | 238    | 187 | 214 | 238    |
| Swept Radius | 130   | 145     | 155    | 153 | 153 | 155    | 153 | 153 | 155    | 130   | 145     | 155    | 153 | 153 | 155    | 153 | 153 | 155    |
|              | 5 1/4 | 5 11/16 | 6 1/16 | 6   | 6   | 6 1/16 | 6   | 6   | 6 1/16 | 5 1/4 | 5 11/16 | 6 1/16 | 6   | 6   | 6 1/16 | 6   | 6   | 6 1/16 |

| Wheel Options | Hub Width x Bore | Bearing Type | Load Capacity  | Diameter x Width   | Tyre Material | Fork Type  | Plate Swivel | Plate Total Brake | Plate Direction Lock | Bolt Hole Swivel | Bolt Hole Total Brake | Bolt Hole Direction Lock |
|---------------|------------------|--------------|----------------|--------------------|---------------|------------|--------------|-------------------|----------------------|------------------|-----------------------|--------------------------|
|               | mm / inches      |              | kg / lb        | mm / inches        |               |            |              |                   |                      |                  |                       |                          |
|               | 40x8<br>1 9/16x8 | Ball         | 150kg<br>330lb | 150x34<br>6x1 5/16 | Grey Rubber   | Wheel Only | /MZP         | /MZPTB            | /MZPDL               | /MZH             | /MZHTB                | /MZHDL                   |
|               | 40x8<br>1 9/16x8 | Ball         | 150kg<br>330lb | 175x34<br>7x1 5/16 |               | MTQ150G    | MTQ150G/MZP  | MTQ150G/MZPTB     | MTQ150G/MZPDL        | MTQ150G/MZH      | MTQ150G/MZHTB         | MTQ150G/MZHDL            |
|               | 40x8<br>1 9/16x8 | Ball         | 150kg<br>330lb | 200x34<br>8x1 5/16 |               | MTQ175G    | MTQ175G/MZP  | MTQ175G/MZPTB     | MTQ175G/MZPDL        | MTQ175G/MZH      | MTQ175G/MZHTB         | MTQ175G/MZHDL            |
|               | 40x8<br>1 9/16x8 | Ball         | 150kg<br>330lb |                    |               | MTQ200G    | MTQ200G/MZP  | MTQ200G/MZPTB     | MTQ200G/MZPDL        | MTQ200G/MZH      | MTQ200G/MZHTB         | MTQ200G/MZHDL            |

www.reflexequip.com.au

REFLEX

MELBOURNE  
(03) 9763 9644  
rowville@reflexequip.com.au

SYDNEY & ILLAWARRA  
(02) 9725 3266  
smithfield@reflexequip.com.au

CENTRAL COAST & NEWCASTLE  
(02) 4324 3455  
gosford@reflexequip.com.au