
















Reflex CASTORS AND WHEELS

General Wheels / core

REFLEX
equip

General wheels		Wheel Specification				
		Wheel Code	Capacity per each	Diameter x Width	Hub Width X Bore	Bearing Type
Utility wheel Puncture free for wheelbarrows, utility equipment, etc. Available with either double sealed precision ball bearings for easiest rolling (max speed 10km/hr) or plain inserted bushes for use where wet conditions may be encountered. Optional bearings in lots of 50 or more. Precision ball 5/8", 3/4" Plain bush 5/8", 3/4"		R250/50C-PRYQ20	150kg 330lb	250x50 10X2"	60x20 23/8"x20mm	 Ball
		R300/50C-PRYQ20		300x50 12X2"		
		R400/70C-PRYQ20		400x70 16x23/4"	80x20 33/16"x20mm	
Solid cushioned wheel Recommended as a puncture proof tyre where broken glass, nails, etc. may cause trouble. Use also on equipment where the tyre must not be flat, e.g. fire extinguisher trolleys or trolleys at a holiday home. It has the size and width to be useful on construction sites. Optional bearings in lots of 50 or more. Precision ball 5/8", 3/4", 20mm		R280/70R-SRBB10	200kg 440lb	280x70 11x23/4"	60x1" 23/4x1"	 Cone
Heavy duty This wheel can also be supplied without the hub and bearings to fit directly onto a Holden HT hub. Ordered as R400X8-SNB This wheel is designed for towing and NOT as a drive wheel.		R400X8-SQ10 available in 410 Series as V21662812	600kg 1320lb	400x95 16x33/4"	80x1" 23/16x1"	 Ball
Hand truck wheels Medium duty offset design for OEM's and replacement markets. Durable and economical crumbed rubber tyre, mounted on a high impact polypropylene centre, fitted with 20mm deep groove bearings as standard.		U200/50C-POYB20	135kg 30lb	200 x50 8x2"	56x20 21/4"x20	 Cone
		U200/60C-POYB20		200x60 8x23/8"		
General purpose rubber utility wheel Used on light lawn equipment, light lawn carts, toys, bottle trolleys, etc. Attachment: 1/2" ratchet caps (RC12) offer a bright nickel finish to the cap. Hold the cap in place with a short length of 22mm OD (1/2") tube supporting the outer rim, and then tap on with a hammer. Always use these on bright steel axles. The PRA and PRB wheels are an offset centre so the axle does not stick out, the PRP is symmetrical. Optional hub cap (GHUBCAP)		PRA125	50kg 110lb	125x36 5x111/16"	38x1/2" 11/2x1/2"	 Plain
		PRB125	75kg 165lb	150x36 6x111/16"		 Cone
		PRA150				100kg 220lb
		PRB150	 Cone			
		PRA200	100kg 220lb	250x45 10x13/4"		 Plain
		PRB200				 Cone
		PRP250				 Plain

www.reflexequip.com.au

REFLEX

MELBOURNE
(03) 9763 9644
rowville@reflexequip.com.au

SYDNEY & ILLAWARRA
(02) 9725 3266
smithfield@reflexequip.com.au

CENTRAL COAST & NEWCASTLE
(02) 4324 3455
gosford@reflexequip.com.au