













Reflex CASTORS AND WHEELS

100-360kg 220-800lb

Pneumatic Wheels-steel / core

2 of 2



Pneumatic wheels - steel core		Tread Pattern	 Diameter x width	 Wheel Code	 Bearing Type ID x width Standard Optional	 Inflation pressure	 Capacity at various speeds		
							8 km/hr 5mph	15KM/hr 10mph	
<p>WARNING</p> <p>The load and cold inflation pressures imposed on the combination of tyre and wheel must not exceed the recommendations, even though the tyre is approved for a higher load or inflation pressure.</p> <p>USE OF PNEUMATIC WHEELS OTHER THAN AS RECOMMENDED CAN BE DANGEROUS. If in doubt the factory for information.</p>			400x100 16x4"	400X8KNO-SB10	 Cone 1" X 107 1x41/4" *5/8", 3/4 or 20mm	210. k.p.a. 30 psi DO NOT over inflate	WARNING- Do not exceed these capacities or speeds	220kg 485lb	200kg 440lb
			330x125 13 1/2x5"	500X6GRA-SB10	 Cone 1" X 107 1x41/4" *5/8", 3/4 or 20mm			130kg 285lb	100kg 220lb
			420x165 16 1/2x6 1/2"	650X8GRA-SB10	 Cone 1" X 150 1x6" *5/8", 3/4 or 20mm			230kg 510lb	200kg 440lb
* ID of bearing is reduced by inserting flanged nylon bush into the standard bearing - add 4mm to hub width									

www.reflexequip.com.au



MELBOURNE
(03) 9763 9644

rowville@reflexequip.com.au

SYDNEY & ILLAWARRA
(02) 9725 3266

smithfield@reflexequip.com.au

CENTRAL COAST & NEWCASTLE
(02) 4324 3455

gosford@reflexequip.com.au