

Scissor Lift Table - Electric Lift - TS HTFG

Remote Power System, easy for controlling, convenient for maintenance. Electronic Controlling Box with UP, DOWN & Emergency Buttons. Electric Controlling System is imported from Europe.



Code	Capacity kg	Min Height mm	Max Height mm	Platform mm	Elevation Time
TS HTFG	1000	82	760	1450 x 1140	8 sec

Scissor Lift Table - Electric Lift - TS HIW4

Made of High Quality Steel and is designed to be durable, reliable and easy to use. Electric Controlling System is imported from Europe. Compact Structure gives balanced lifting and lowering. Large Capacity.



Code	Capacity kg	Min Height mm	Max Height mm	Platform mm	Elevation Time
TS HIW4	2000	190	1010	1300 x 800	40 sec

Scissor Lift Trolley - Powerlift DCD100

The DCD100 reaches to 1482 mm and is an ideal lifting aid for any product that must be raised to higher shelves or racking; it's ideal to stack supermarket shelves.



Ideal for environments where hydraulics can't be used



Code	Capacity kg	Min Height mm	Max Height mm	Platform mm	Elevation Time
ST DCD100	100	512	1428	895 x 480	20 sec

Scissor Lift Trolley - Powerlift DC250

DC 250s with a lift of 855mm have been adapted for use as baby change tables in day care and crèche facilities, dog grooming tables and a multitude of office and factory applications. Lifting is made quick and easy with this quiet, clean, battery powered unit. Greatly reduces the risk of injury from bending and lifting.





High duty cycle, rechargeable battery, up to 150 lifts per charge.

Code	Capacity kg	Min Height mm	Max Height mm	Platform mm	Elevation Time
ST DC250	250	365	855	895 x 480	20 sec

Scissor Lift Trolley - TS TF15

The Reflex range of hydraulic scissor lift trolleys is designed to provide improved ergonomic conditions to ensure the health, safety and comfort of the operator.



Code	Capacity kg	Table Height Range mm	Platform mm	Handle Height mm
TS TF15	150	220 - 750	700 x 450 x 36	950

Scissor Lift Trolley - TS TF75

The Reflex range of hydraulic scissor lift trolleys is designed to 1000×510 deck, 750kg capacity. Manual Push. Precision hydraulic foot pump. Quick release system.



Code	Capacity kg	Table Height Range mm	Platform mm	Handle Height mm
TS TF75	750	420 - 900	1000 x 510 x 55	1000

Scissor Lift Trolley - TS TF30 & TS TF50



Code	Capacity kg	Table Height Range mm	Platform mm	Handle Height mm
TS TF30	300	285 - 880	815 x 500 x 50	990
TS TF50	500	285 - 880	815 x 500 x 50	990

Scissor Lift Trolley - TS TG50 & TS TG100



Code	Capacity kg	Table Height Range mm	Platform mm	Handle Height mm
TS TG50	500	286 - 915	1600 x 810 x 55	990
TS TG100	1000	360 - 1400	2050 x 750 x 55	990



Scissor Lift Trolley - TS TFD35

Positive braking system on rear wheels for safety. Very manoeuvrable. Manual Push. Precision hydraulic foot pump. Quick release system.



Code	Capacity kg	Table Height Range mm	Platform mm	Handle Height mm
TS TFD35	350	355 - 1300	910 x 500 x 53	975

4

Scissor Lift Trolley - Electric - TS ETF50

Electric Trolley with precision hydraulic pump and lockable wheels.

- ✓ Electric Lifting.
- Great for loads up to 500kg.
- Outstanding lift and lowering speeds.
- ✓ Lifts to over 1m.



Code	Capacity kg	Table Height Range mm	Platform mm	Handle Height mm
TS ETF50	500	440 - 1025	1010 x 520 x 50	970

Scissor Lift Trolley - TS TF200

Hydraulic Scissor Lift Trolleys provide a safe and efficient method of lifting & transporting loads with improved productivity and efficiency in the work place. Features 200mm rubber wheels for excellent performance on uneven or rough terrain.



Code	Capacity kg	Table Height Range mm	Platform mm	Handle Height mm
TS TF200	200	345 - 1010	1000 x 500 x 35	1050

Scissor Lift Trolley - TS TFD70

Positive braking system on rear wheels for safety. Very manoeuvrable. Manual Push. Precision hydraulic foot pump. Quick release system.



Code	Capacity kg	Table Height Range mm	Platform mm	Handle Height mm
TS TFD70	700	450 - 1500	1220 x 610 x 53	1015

Scissor Lift Trolley - Electric - TS ETFD35

Double Scissor lift action, the Electric Scissor Lift Trolleys is designed to provide improved ergonomic conditions to ensure the health, safety and comfort of the operator.



Code Capacity kg		Table Height Range mm	Platform mm	Handle Height mm
TS ETFD35	350	370 - 1300	910 X 500 X 53	920

Scissor Lift Trolley - Stainless Steel - TS TF50S

Foot operated Hydraulic lift. 450kg capacity. Precision hydraulic foot pump. Quick release system. Positive Breaking Systems. Handle folds flat for easy storage.



Code	Capacity kg	Table Height Range mm	Platform mm	Castor Wheel mm
TS TF50S	450	290 - 890	815 X 500	125 x 40

Scissor Lift Trolley - Stainless Steel - TS TFD15S



Code	Capacity kg	Table Height Range mm	Platform mm	Castor Wheel mm
TS TFD15S	100	250 - 1220	700 X 445	100 x 25

Scissor Lift Trolley - Stainless Steel - TS TFD35S



Code	Capacity kg	Table Height Range mm	Platform mm	Castor Wheel mm
TS TFD35S	350	355 - 1300	910 X 500	125 x 40

Pallet Truck - Pallet Jack - Narrow/Standard



Code	Width mm	Length mm	Height mm	Capacity kg	
TS AC25-450	450	1150	75-185	2500	
TS AC25-520	520	1150	75-185	2500	
TS AC25-685	685	1150	75-185	2500	
Use for Standard "Chep" pallet width					

Pallet Truck - Pallet Jack - Super Long



Code	Width mm	Length mm	Height mm	Capacity kg		
TS ACL20-685	685	1800	75-190	2000		
Use for Standard "Chep" pallet width						

Pallet Truck - Pallet Jack - Braked - Standard

For loading and unloading goods in warehouse, docks and factories.



Code	Width mm	Length mm	Height mm	Capacity kg		
TS AC20HO	685	1150	85-200	2000		
Use for Standard "Chep" pallet width						

Pallet Truck - Pallet Jack - Galvanised



Code	Width mm	Length mm	Height mm	Capacity kg
TS ACZ20L	685	1150	75-190	2000

Pallet Truck - Pallet Jack - Low Boy



Code	Width mm	Length mm	Height mm	Capacity kg	
TS ACLOW-540	540	1150	51-165	2000	
TS ACLOW-685	685	1150	51-165	2000	
Not suitable for CHEP pallets					
Perfect for moving low entry skids with a low height of 51mm.					

Pallet Truck - Pallet Jack - Stubbie - Narrow



Code	Width mm	Length mm	Height mm	Capacity kg
TS AC25-450/800	450	800	75-190	2500
TS AC25-520/800	520	800	75-190	2500

Pallet Truck - Pallet Jack - Scales - Standard

A great alternative for users who need pallet weights for transportation.



Code	Width mm	Length mm	Height mm	Capacity kg
TS WAQ25E540	540	1150	88-200	2000
TS WAQ25E685	685	1150	88-200	2000

Pallet Truck - Pallet Jack - Stainless Steel



Code	Width mm	Length mm	Height mm	Capacity kg
TS ACS20-685	685	1150	75-190	2000

Skid Lifter - 1000kg Electric

This Electric Skid Lifter features 1000kg capacity and a reliable 12V/60Ah battery with 0.8Kw power unit for easier & faster lifting. Welded steel frame & forks handle heavy loads with ease. Also suitable as a lift table or work bench.



Code	Width mm	Length mm	Height mm	Capacity kg	
TS EX-685	680	1170	85-800	1000	
Not suitable for "Chep" pallet width.					

Lifter - Platform Stacker

Foot pedal pump operation. Overload protection valve equipped. Hard chrome plated frame. Double frame rollers and double steering rollers ensures a stable and safe operation.



Code	Capacity kg	Lift Range mm	Platform mm	LxWxHmm
TS FP0415	400	200 - 1500	590 x 650	1015 x 590 x 1630

Lifter - ML1 Series

This Mast Lift Trolley has been designed with constantly lifting heavy items from the floor to benches and from the rear of vehicles. Perfect for Lifting and Transporting heavy loads.

- \checkmark Stylish Design
- Easy to transport folds and unfolds in 30 seconds.
- Patented, silent winch
 locks the load at any height.
- Steel cable inside mast for safety (prevent pinch points).
- √ 250mm puncture proof, light-weight wheels - good traction and smooth ride even over rough terrain.



Code	Capacity	Lift Height	Width x Depth mm	Height mm
MA ML1	120kg	1050mm	710 x 510	1370

Skid Lifter - Manual

Skid Lifters reduce unnecessary bending thus improving material handling productivity, increasing efficiency and reducing potential worker injury. With a 1000kg capacity this Skid Lifter is suitable as a lift table or workbench. Stabilisers ensure maximum stability.



Code	Width mm	Length mm	Height mm	Capacity kg
TS HLTN10540	540	1150	85 - 800	1000
TS HLTN10680	680	1150	85 - 800	1000

Lifter - Hyloader Minilift

The MiniLift is rated to safely handle 200kg at a 350 mm load centre and uses a 24 volt battery circuit for lifting and lowering. No 'metal to metal' contact at the mast/carriage assembly which eliminates any foreign particles migrating into your process, ideal for use in Food, Beverage, Pharmaceutical applications.

It features an electronic overload protection to prevent operators lifting above the rated capacity.

- Hospital Warehouse Library -Laboratory - Catering - Factory
- ✓ Max load 200kg
- √ 6 hour recharge
- √ 185 lifts per charge (100kg)
- ✓ Electronic overload protection
- √ Polyurethane tyred wheels
- Three 'Ramp Speed' variants to tailor lift speed acceleration in critical applications or where loads being handled are very sensitive.

Code	Capacity	Lift Height	Platform Size mm	L x W x H mm
HY MLSTDBC	200 kg	100-1400mm	600 x 550	860 x 580 x 2020

Lifter - Mini Aluminium Hand Stacker

The lifters have the versatility of a hand truck but with the ability to raise loads of up to 90kg by means of an easy wind up winch. Folds and loads easily into a ute or station wagon.

- Quickly convert from a lifter to a platform trolley.
- Easy Disassembling and assembling.
- $\checkmark \;\;$ Lifting runners with flanged rollers, operated with safety winch.
- Manoeuvrable, powerful lifting devices-can be used for any lifting work.
- \checkmark Fit into smaller spaces when disassembled.
- ✓ Light Aluminium mast, easy handling.
- ✓ Lift by winch.
- ✓ The best brake function with special design.
- √ The right mini-lifter for every load.







Code	Capacity kg	Lift Height mm	Table Size mm	Folded Size L x W x H mm	N.W.
TS DEP90	90	25 - 1500	355 x 420	559 x 360 x 1125	30kg

Lifter - Electric Transporter - TS MES150

The MES150 Electric Lifter suits a wide variety of applications.

- Highly manoeuvrable and lightweight
- ✓ Swivel castors fitted with foot brakes
- Easy to use up and down switching

Model	TS MES150
Capacity	150 kg
Lifting Height	1550 mm
Fork Height	130 mm
Fork Overall Width	460 mm
Fork Length	460 mm
Front wheel	Φ75*32 mm
Rear wheel	Ф100*32 mm
Lifting speed full load/no load	70/83 mm/s
Lowering speed full load/no load	101/85 mm/s
Battery	12V / 7Ah
Motor	12 V
Weight	58 kg
Warranty	1 year



Platform Lifting Trolley

Platform Lifting Trolleys are ideally suited to unloading skids up to 400kg in smaller workshops and warehouses, hospitals and assembly lines. All models have a powder-coated finish and are fitted with both overload valve and slow lowering valve to control speed as well. All models are available with a choice of manual foot pump hydraulic actuation or battery powered electro hydraulic lift.



- High quality, heavy duty construction for reliability.
- Available in a variety of lift heights to suit many applications.
- Top quality, heavy load bearing castors ensure durability.
- Supplied with both a removable work platform and fork tynes.
- Manual and battery powered models available.
- Fitted with rear swivel brake wheels as standard to prevent the table from moving whilst loading and unloading.
- ✓ Adjustable tyne width.

Manual Code	PH PHK1200	PH PHK1500	PH PHK1700				
Model PHK	1200	1500	1700				
Max Load kg	400	400	400				
Operation	Manual	Manual	Manual				
Length mm	1050	1050	1050				
Width mm	595	595	595				
Height mm	1435	1730	1925				
Platform mm	650 x 580	650 x 580	650 x 580				
Lift Height mm	1200	1500	1700				
Min Height mm	90	90	90				
Tyne Length mm	645	645	645				
Tyne Width mm	110	110	110				
Exterior width mm	550	550	550				
Net weight kg	84	89	93				
Electric Code	PH PHK1200E	PH PHK1500E	PH PHK1700E				
Net weight kg	128	135	138				
Same s	pecification as manual m	Same specification as manual models except for Net Weight					

Lifter - Hyloader Multilift

The Hyloader Multilift is a multi-purpose lift truck capable of performing various lifting operations simply by exchanging attachments.

A single mast design and diagonally opposed roller carriage system provides excellent load stability and unobstructed vision.

The MultiLift can be manufactured with almost any base configuration together with various mast height options. Standard attachments include Fixed Forks, Adjustable Forks, Slip-On-Platform or a three position Jib.





FIXED FORKS Blade:600L x 75W x 75H Lowers to 100mm Raises to 1580mm Inside Width: 500mm Outside Width: 650mm Weight: 15kg



ADJUSTABLE FORKS Blade:600L x 75W x 20H Lowers to 20mm Raises to 1500mm Inside Width: 6mm to 500mm Outside Width: 156mm to 650mm Weight: 34kg

REEL HANDLER

- √ Heavy duty load brake winch
- Polyurethane tyred roller bearing wheels
- √ Wheels 100mm front, 125mm rear
- √ Positive foot operated brake
- ✓ Lift height & base dimensions can be modified to order
- ✓ Special purpose attachments available
- ✓ Weight 54kg



DRUM TIPPER



SLIP ON PLATFORM
To suit fixed or adjustable forks
Length: 700mm
Width: 700mm
Thickness: 3mm
Weight: 14kg



CRANE JIB Lowers to 630mm Raises to 2100mm Max. Load at reach 350kg at 350mm 300kg at 450mm 250kg at 550mm Weight:9kg

Code	Attachments	Code	Attachments
HY HMBODY	Basic Unit	HY HMPLAT	Slip On Platform
HY HMFORKADJ	Adjustable Forks	ну нмноок	Crane Jib
HY HMFORKFIX	Fixed Forks		



Mast Lift Trolley - Hand Winch - Hand Stacker

Lightweight Winch Operated Stacker that's ideal for Tradespeople.

The compact design allows you to lift and manoeuvre in tight work areas and spaces and folds and loads easily into a ute or station wagon. 181kg Load Capacity.

Mast Lift Trolley Features:

- ✓ Lightweight stacker
- √ Foldable forks
- ✓ Easily loads into a ute or van
- ✓ Compact manoeuvrable design



Standard Steel Lifter Feature:

- ✓ Overall Size: 880 x 570 x 1545mm.
- √ Thick steel sheet platform.
- Large size wheels for easier manoeuvrability.
- Robust frame.
- Precision Quality hydraulic pump.
- ✓ Light weight 80kg.



Code	Width mm	Length mm	Height mm	Capacity kg
TS WFH181	630	570	90-2400	181

Code	Lift Range mm	Platform Size mm	Overall Height mm	Capacity kg
TS 3W219	10-1350	560 x 560	1545	340

Mast Lift Trolley - Manual - Hand Stacker

Suitable only for open based pallets.

This versatile Hand Stacker has up to a large 1500kg capacity and a 2500mm lift.

Featuring precision hydraulics and foot or hand pump action.

Mast Lift Trolley Features:

- √ Able to straddle pallets.
- ✓ Large 1500kg capacity.
- ✓ Manual Push.



TS SFH15 &TS SFHD10

Code	Fork Size mm	Fork Length mm	Fork Height Range mm		Mast Height Min. mm	Capacity kg
TS SFH15	150/160 x 60	1200	85-1600	300-740	1980	1500
TS SFHD10	150/160 x 60	1200	85-2500	300-740	1830	1000
TS SFH10W	150/160 x 60	900	85-1600	300-1360	1980	1000

Mast Lift Trolley - Hand Winch - Hand Stacker

High quality aluminium hand winch platform trolley that features a maximum working height of 5 metres.

Rolls easily through single doorway in upright position and quick and easy setup that requires no tools.

Mast Lift Trolley Features:

- ✓ Heavy duty design.
- Rolls easily through single door in upright position.
- Quick setup requires no tools.
- Interchangeable load handling attachments.
- ✓ Compact design, legs fold up for easy storage.
- ✓ Aluminium Stacker.



Code	Capacity kg	Max. Working Height mm	Overall Length mm	Weight kg
TS MER35	350	3500	1500	120
TS MER50	300	5000	1880	145

TS SFH10W

Mast Lift Trolley - Electric - Platform Stacker

This wide leg straddle platform stacker is ideally suited to unloading skids in smaller workshops and warehouses, hospitals and assembly lines. It features an adjustable fork with and electromagnetic service brake.

Electric Mast Lift Platform Lifting Trolley Features:

- ✓ Huge 2840mm maximum lift height
- ✓ Adjustable Fork Width
- ✓ Electromagnetic Service brake
- ✓ 2 x 12V/85Ah batteries



Code	Width mm	Length mm	Fork Height mm	Mast Height Min. mm	Capacity kg
TS ECL1029M	1400	1150	2840	1950	1000

Mast Lift Trolley - Electric - Platform Stacker

The EPS0415 Electric Mast Lift Trolley suits a wide variety of applications. The special design of this Electric Mast Lift Platform Stacker combines lifting, transporting and stacking function together. Whether to shift paper reels in an office, transfer heavy lab equipment or unload trucks in a warehouse this Electric Mast Lift Trolley can do it all with ease & safety.

Electric Mast Lift Trolley Features:

- ✓ Electrical Lift Manual Push Operation.
- Quality batteries.
- √ 400kg capacity.
- ✓ Braked Rear Wheels for security.



Model	TS EPS0415
Capacity (kg)	400kg
Fork Height Range (mm)	85 - 1500mm
Platform Size (Length x Width)	650 x 576mm
Caster Dia. (mm) (PU)	Ф127x40mm
Front roller Dia. (mm) (PU)	Ф75x40mm
Battery (V/Ah)	DC12V/60Ah
Motor (V/W)	DC12V/700W

Hydraulic Lifter - Furniture Mover

For professional transport of heavy items. The Furniture Movers make moving awkward items a breeze. These Movers take up to 600kg capacity and lift to 300mm in height.



TS NFM180

TS NFM60

Code	Wheels mm	Lift Height mm	Capacity kg
TS NFM60	145	300	600
TS NFM180	145	250	1800

Waste Bin Mover

The Waste Bin Mover consists of an applicable Waste Bin Trolley and a suitable Electrodrive Tug and is an ideal solution for facilities with multiple waste bins (80-360 litre wheelie bins) that need to be regularly moved for emptying.



EL MODULAR3

Code	Description	
EL MODULAR3	3 Bay Trailer	Codes are for the applicable
EL MODULAR6	6 Bay Trailer	Waste Bin Trolley only. A suitable Electrodrive Tug is required.

Gzunda Bed Mover

The Gzunda Bed Mover allows one person to effortlessly move heavy hospital beds with or without patients between wards and departments or to and from theatre and medical imaging.



Code	Capacity kg	L x W x H mm	Weight kg	Voltage	Range km
EL GZ10SL	500	1190 x 780 x 1126	130	24	10



Tug Compact

The Tug Compact is perfect for moving document trolleys around universities, transporting medical carts around hospitals or moving bins and linen trolleys.

The tiller handle allows the operator to walk in front of the load, reducing strain on the lower back, shoulders and legs, whilst maximising forward vision to reduce the possibilities of collisions.

- Move trolleys or wheeled objects weighing up to 500kg
- ✓ Easy attachment to trolleys
- Quiet, smooth operation with zero emissions
- ✓ Low maintenance
- ✓ Simple to use, no driver's licence required



Code	Capacity kg	Weight kg	Voltage	Approx Range km
EL TUGCOM500NH	500	110	24	10

Tug Evo

The Tug EVO allows a single operator to quickly and easily hitch to a load and move it. Steering with the tiller handle allows the operator to walk in front of a heavy load, reducing strain on the lower back, shoulders and legs, whilst maximising forward vision to reduce the possibilities of collisions.

Typical applications include moving trolleys through airports, factories or institutions, transport of stillages around a facility and moving specialist equipment.





Code	Capacity kg	Voltage	Weight kg	Range km
EL TUGEVO1TNH	1000	24	165	12
EL TUGEVO2TNH	2000	24	200	12

Tug Tough

Built with heavy industrial applications in mind, the Tug Tough utilises a powerful 48V drive system to allow a single operator to hitch to and move big loads. It is available in 10 tonne capacity, with an optional hydraulic lifting hitch available.

Typical applications include: 🕞

- Moving truck and mining engines around the workshop.
- Pulling buses or trucks through a production line.
- Towing aeroplanes in and out of hangers
- ✓ Aerospace maintenance.



Code	Capacity kg		Lift Capacity kg	IVWVHmm	Weight kg	Range km
EL TUGTOUGH10TNH	10000	Yes	5000	1910 x 750 x 995	390	12

Load Restraint - 4 metre Weekender

Lightweight and versatile this unit features 25mm ratchet assembly with PVC coated "S" hooks. It is well suited to general light duty applications including marque tie down, bundling product and roof racks.



	Code	Lashing Capacity kg	Pretension kg	Length mm
S	S B1WEEKEND	250	125	4000

Load Restraint - 6 metre Tradesman

Features 35mm ratchet assembly fitted with "S" hooks, a wide handle for better grip and lock down safety. Ideal for utilities, box trailers etc..



ĺ	Code	Lashing Capacity kg	Pretension kg	Length mm
	SS D1TRADES	500	250	6000

Replacement Strap

Ratchet Tie Down Load Restraint replacement strap fitted with heavy duty hook and keeper. Fully Certified AS4380.



A Lashing Capacity (LC) is the maximum safe load weight recommended for a tie down. Overloading may result in failure.

Code	Size mm	Length m	Lashing Capacity kg
GR GLS5009	50	9	2500
GR GLS5011	50	11	2500
GR GLS5013	50	13	2500

Ratchet Tie Down - Load Restraint



Code	Size mm	Length m	Lashing Capacity kg
GR GLR255	25	5	750
GR GLR356	35	6	1500
GR GLR509	50	9	2500
GR GLR5013	50	13	2500
GR GLR759	75	9	5000

Pallet Positioner - Ez Loader

Generally automatic, self levelling and self contained, Pallet Positioners are designed for loading and unloading of palletised materials.

Integral turntables eliminate reaching, providing advanced ergonomic benefits.

EZ Loader Pallet Positioners are excellent additions to any loading or unloading process using pallets as the transportation medium.

Pallet Positioners can help reduce worker fatigue, improve safety and minimize situations which can lead to back injuries or damage to sensitive products.

Typical applications for Pallet Positioners are in manufacturing, processing and distribution.

Pallet Positioner Features:

- Self-levelling design automatically keeps the top of the load at a convenient working height to help eliminate bending and improve productivity
- Integral rotator ring helps eliminate reaching and stretching
- ✓ Infinitely adjustable for varied loads by simply adding or bleeding air
 no changing of springs required
- Pressure gauge and air valves are protected, yet located for easy access.
- Secured ball-bearing centre pivot of the 1092mm dia. rotator ring provides smooth, even rotation
- ✓ Pressure relief valve prevents excess pressure build-up
- Rollers are entrapped in the base frame and platform for added stability











Code	Travel mm	Height Lowered/Raised mm	Capacity Min/Max kg
BJ EZYLOADER	488	267/775	113/1588

Pallet Positioners - Palift

This Palift Pallet Positioner has a turntable top for rotating the load for easy access.

Pallet Positioners resemble scissor lift tables in appearance. They have a top deck and a base connected by a pair of scissor legs. The levelling mechanism is a set of springs set to the weight and height (the density) of the product. Pallet Positioners work automatically and raise or lower as the weight changes.

Load setting is a simple process and for most users, springs never have to be changed. A shock absorber prevents any bounce and all Australian Palift Pallet Positioners are supplied with a standard galvanised finish.


A Palift Pallet Positioner is one of the best way to save workers' backs. They automatically keep pallet or stillage loads at an optimum working height when loading or unloading goods. They dramatically reduce the effort required to palletise goods. The proven design is incredibly robust and can last more than 15 years of daily use without maintenance.

Palift Pallet Positioners increase productivity, reduce injuries and improve work force morale.

Palift Turntable Top Pallet Positioner Features:

- ✓ Productivity gains of up to 40%.
- Built-in turntable allows simple load rotation and access to all sides.
- ✓ Standard adjustable feet to allow levelling on uneven surfaces
- ✓ Durable and tough, Palift is galvanised and suitable for washdown.
- ✓ Lifetime spring warranty and 3 year frame warranty.







Code	Platform mm	Height Min/Max mm	Load Range kg		
ST PTG3	Turntable Top 1100 dia	239/709	250/2000		
ST PST3	Static Top 1046 x 1060	225/709	250/2000		
ST PMDB	Mobile Base Frame				
ST PMDH	Mobile Dolly Handle				



Pallet Positioner - 2000kg - Galvanised

Galvanised Finish. Suitable for use in the Food Industry, Dairy and all areas where corrosive acids and saline solutions are used.

Keeps the active layer of the load at or above waist height, eliminating bending and lifting, helping to reduce LTI cause by strains and repetitive movement.

Pallet Positioner Features:

- ✓ One of the best way to save workers backs.
- Automatically keeps pallet or stillage loads at an optimum working height when loading or unloading goods.
- ✓ Dramatically reduces the effort required to palletise goods.
- ✓ Built-in turntable allows simple load rotation and access to all sides.
- ✓ No ground fixing required.
- ✓ Galvanised Finish.



Code	Platform Dia. mm	Base Size mm	Compressed Hight mm	Extended Height mm	Capacity kg
TS PLG1G	1110	920 x 930	240	705	200-2000

Pallet Positioner - 2000kg - Closed Top

Keeps the active layer of the load at or above waist height, eliminating bending and lifting, helping to reduce LTI cause by strains and repetitive movement. The leveller utilises a scissor type action with varying spring combinations that can be adjusted to provide load capacities up to 2000kg. A Low Friction Bearing supported turntable assists in load rotation.

Pallet Positioner Features:

- One of the best way to save workers backs.
- Automatically keeps pallet or stillage loads at an optimum working height when loading or unloading goods.
- ✓ Dramatically reduces the effort required to palletise goods.
- Built-in turntable allows simple load rotation and access to all sides.
- ✓ No ground fixing required.



Code	Platform Dia. mm	Base Size mm	Compressed Hight mm	Extended Height mm	Capacity kg
TS PLG1C	1110	920 x 930	240	705	200-2000

Pallet Positioner - 2000kg - Turntable Top

Keeps the active layer of the load at or above waist height, eliminating bending and lifting, helping to reduce LTI cause by strains and repetitive movement. The leveller utilises a scissor type action with varying spring combinations that can be adjusted to provide load capacities up to 2000kg. A Low Friction Bearing supported turntable assists in load rotation.



Code	Platform Dia. mm	Base Size mm	Compressed Hight mm	Extended Height mm	Capacity kg	Weight kg
TS PLG1	1110	1150 x 934	270	710	200-2000	168

Pallet Turntable - Palring

The Palring is an affordable, easy to use Pallet Turntable ideal for use alongside conveyor, feeding hoppers, extruder, process and production equipment.

Other applications for the Palring Pallet Turntable include, manual palletising / de-palletising and loading / unloading stillages, bins etc.



- ✓ Won't bind or tighten under load.
- ✓ Internal carry handles for easy relocation.
- √ Galvanised
- √ Easy to rotate
- √ 2,000 kg capacity



Code	Capacity kg	Turntable Height mm	Turntable Diameter mm
ST PALRING1	2000	60	1100
ST PALRING2	2000	60	900

